

HIGHLANDER II WITH ENCLOSURE

VERTICAL PLATFORM LIFT ENCLOSURE KIT



Vertical Platform Lifts are required to be enclosed when they have a lifting height of 60" or above for commercial applications and/or when they penetrate a floor. The enclosure kit allows for an integrated solution instead of constructing a hoistway.

KEY AVAILABLE FEATURES:

- Choice of acrylic or steel panels
- Acrylic roof with ventilation system
- Steel frame with SealKor powder coat
- 6' 8" lower door and upper landing gate
- Through-bolt fastening system for enhanced rust protection



HIGHLANDER II WITH ENCLOSURE PRODUCT SPECIFICATIONS

WEIGHT CAPACITY	- 750 lb	SPEED	- 9.5 to 15 FPM
DRIVE	- ACME screw - 90V 2/3 HP fully sealed DC gear motor	POWER	- 120V AC - 15 AMP circuit breaker
PLATFORM SIZES	- 36" x 60" clear platform with 42" guard panel - 42" x 60" clear platform with 42" guard panel	WARRANTY	- 3-year
CERTIFIED	- ETL listed - CSA B44.1/ASME A17.5-2019 - Safety standard ASME A18.1-2020 - Rated commercial and residential	FEATURES	- 4" x 5" constant pressure paddle control - Seal-Kor powder coat with stainless steel hardware for outdoor use
SAFETY FEATURES	- 4-LED indicators in top cap - Emergency stop button in platform - Overspeed brake - Overload protection - Interlocks for doors/gates - Manual lowering tool	OPTIONS	- Battery backup UPS system - 36" or 42" upper landing door with EMI interlock - Grab bar in platform - Key lock in platform - Fire-rated doors - Safety pan - Wired or wireless call/send control - Lighted E-Stop with alarm - 3-stop with 3-button control panel